




SuperTran Cryostats

ST-500 and ST-500UC optical microscopy cryostats

The Lake Shore **ST-500** and **ST-500UC** are the premier low-vibration cryostats for microscopy, imaging, and high spatial resolution photoluminescence. Both models offer short working distance (for use with high magnification optics), nanometer-level vibration and positional drift, and convenient mounting to common microscope stages. They can be combined with the RGC4 recirculating cooler for cryogen-free operation.



ST-500 and ST-500UC optical microscopy cryostats

The Lake Shore SuperTran ST-500 and ST-500UC cryostats from Lake Shore Cryotronics provide variable temperature sample cooling combined with nanometer-level vibrations, and are ideal for microscopy applications including micro-Raman and micro-PL. The ST-500 is optimized for use with either LHe or LN₂, while the ST-500UC is ideal for routine LN₂ use, with occasional operation using LHe.

Both cryostats offer working distance (from microscope objective lens to sample) as small as 1 mm. The sample can be accessed and exchanged from the top of the cryostat without the need to disassemble the cryostat or remove it from the microscope. The ST-500 offers transmission geometry, and both models can be equipped with a variety of window materials.

The ST-500 or ST-500UC can be combined with the RGC4 recirculating gas cooler for fully cryogen-free operation throughout the entire temperature range. The RGC4 enables unattended cryostat operation, ideal for extended duration measurements.

A vacuum shroud extension option permits the ST-500 and ST-500UC to fit within restricted spaces (such as in a superconducting magnet bore or electromagnet pole gap), while the LGV large vacuum shroud option enables mounting very large samples (such as semiconductor wafers) or multiple samples simultaneously.

Key features

Sample-in-vacuum configuration, with continuous operation using the included high-efficiency transfer line

Optional DC and RF wires and cables for electrical measurements

Sample is easily accessed from the top of the cryostat

Top window provides optical access, with objective lens to sample working distance as little as 1 mm

Continuous temperature range from 3.5 K to 475 K (ST-500) or 6 K to 475 K (ST-500UC)

Compatible with RGC4 recirculating gas cooler for cryogen-free operation

Spare o-ring sealed ports accept DC and RF electrical feedthroughs

Variable temperature sample mount and sample holder, with temperature regulated by internal heater and calibrated silicon diode (and external temperature controller)

ST-500/ST-500UC

Featured components

19 mm (0.75 in) diameter copper sample mount

Integrated control heater and calibrated silicon diode control sensor

High-efficiency, flexible LHe/LN₂ transfer line

152 mm (6 in) vacuum shroud with epoxy-sealed UV-grade fused silica top window, 25 mm (1 in) clear view by 1.6 mm thick

Epoxy-sealed UV-grade fused silica bottom window, 25 mm (1 in) clear view by 1.6 mm thick (ST-500 only)

Integrated supply and return bayonets

10-pin electrical feedthrough, spare o-ring sealed feedthrough port, evacuation valve, and safety pressure relief valve (ST-500-UC); ST-500 top plate can lift in the case of over-pressure

Selections

Working distance

ST-500: 1 mm to 31 mm

ST-500UC: 1 mm to 7 mm

Transfer line

6 ft (182.8 cm) standard flex length

Custom flex length [consult Lake Shore](#)

Right angle leg(s) [consult Lake Shore](#)

Easily add DC, AC, and mixed DC+AC measurement capabilities to your cryostat with an M81-SSM

This modular, multichannel system provides highly synchronized DC, 100 kHz AC, and mixed DC + AC sourcing and measuring — including both voltage and current lock-in measurement capabilities — for low-temperature material research performed in your cryostat. It supports up to three remote-mountable source and three measure modules per a single M81-SSM-6 instrument and, owing to its modularity, allows signal and source amplifiers to be located as close as possible to the sample being characterized. This minimizes the signal wiring to the sample, reduces noise, and increases measurement sensitivity. The modules also leverage patent-pending MeasureSync™ real-time sampling technology to ensure synchronous sourcing and measuring across all channels. Plus, by having both DC and AC sourcing and measurement in one instrument, the M81-SSM can eliminate the need for mixed-instrument setups, greatly simplifying the setup of complex characterization configurations.



Real-time sampling architecture for synchronous sourcing/measuring

All source and measure channels are capable of DC and AC to 100 kHz signals

100% linear circuitry for the lowest possible source/measure noise

Optimized for fundamental, harmonic, and phase AC plus DC biased measurements

Unique, flexible instrument/distributed module architecture

Provides the absolute precision of DC plus the detection sensitivity performance of AC instrumentation

Uses a clean, simple UI and common programming API for fast setup

Included MeasureLINK software enables full end-to-end measurement and cryostat temperature control

MeasureLINK™

Options

Windows

Custom window options are available, including IR-grade fused silica, diamond, polyethylene, beryllium (dome or disc), KBr, or KRS-5. Contact Lake Shore for more information.

UV-grade fused silica: 10 mm clear view by 0.5 mm thick
[WT-ST-500-020-FS](#)

ZnSe: 25 mm clear view by 1.6 mm thick [WT-ST-500-062-ZNSE](#)

Sapphire: 25 mm clear view by 0.5 mm thick
[WT-ST-500-020-SAPPHIRE](#)

CaF₂: 25 mm clear view by 2 mm thick [WT-ST-500-080-CAF2](#)

Snout extension

For permanent magnet [ST-500-EXT-PM](#)

For bore of superconducting magnet [ST-500-EXT-SCON](#)

For pole gap of electromagnet [consult Lake Shore](#)

Other options

The modular ST-500 cryostat can be customized with different vacuum shroud designs to suit your unique application. Options include adding a large vacuum shroud extension (ST-500-LGV) for added space inside the sample area, or the addition of nanopositioners (ST-500-NANO). Contact Lake Shore to discuss your specific requirement

Cooled radiation shield window (ST-500 only)
[WT-ST-500-SHIELD](#)

Sample holders

Special sample holders are also available, including diamond anvil cell (DAC) and resistivity options. Contact Lake Shore for more information.

DIP (with cooled radiation shield window)

For total control of measurements performed in a cryostat, add our MeasureLINK software

Our optional MeasureLINK software enables a wide range of capabilities including charting and logging, system monitoring with a cryostat-specific process view, and even controlling Lake Shore equipment as well as some third-party instrumentation, in a non-programming environment. You can also create unlimited functionality using the scripting development environment.

Create multiple configurations to support separate measurements

Monitor temperature and change setpoints with the monitor pane


Easily create nested, multi-level measurement loop sequences

See real-time internal cryostat temperatures in Process View

Charts and log all system variables with Chart Recorder

No programming required — drag and drop to create temperature sweeps, access measurements, and add third-party instruments


Custom scripting function allows you to construct new and edit existing measurement scripts



The chart recorder utility enables charting and logging of all system variables, for example, so you can keep a close eye on temperature trends in a cryostat experiment in real-time; it also helps you determine when steady-state conditions have been reached.

MeasureLINK
Monitor Pane

MeasureLINK™



Options

Electrical feedthroughs

(1) BNC grounded	EF-BNC-1-B-AL
(2) BNC grounded	EF-BNC-2-S-AL
(6) BNC grounded	EF-BNC-6-G
(1) BNC insulated	EF-BNC-1-B-NC
(2) BNC insulated	EF-BNC-2-S-NC
(6) BNC insulated	EF-BNC-6-I
(1) triaxial grounded	EF-TRIAX-1-B-AL
(6) triaxial grounded	EF-TRIAX-6-G
(1) triaxial insulated	EF-TRIAX-1-B-NC
(6) triaxial insulated	EF-TRIAX-6-I
(2) SMA grounded	EF-SMA-2-B-AL
(6) SMA grounded	EF-SMA-6-G
(2) SMA insulated	EF-SMA-2-B-NC
(6) SMA insulated	EF-SMA-6-I
10-pin	10P-ASSEMBLY
19-pin	19P-ASSEMBLY
26-pin	26P-ASSEMBLY
32-pin	32P-ASSEMBLY

Additional temperature sensors

One Lake Shore calibrated diode is now included on every cryostat as the control sensor

Silicon diode, calibrated	DT-670-CU-HT-1.4L
Cernox® magnetic field independent, calibrated	CX-1050-CU-HT-1.4M


Installed wiring

(1), (2), or (6) coaxial cables, SMA	CABLEASSY-63340
(1), (2), or (6) coaxial cables, BNC	CABLEASSY-63342
(1) or (6) triaxial cables	CABLEASSY-63341
(10), (19), (26), or (32) PhBr wires	WIRE-PHBR

Accessories

Available at www.lakeshore.com

LHe storage Dewar	CF-100
LN ₂ storage Dewar	LN-50
Vacuum pumping station	10RVP, 10DDP, or TS-85-D
Temperature controller	325, 335, or 336



Cernox CU-HT sensor




336 temperature controller

Specifications



ST-500



ST-500UC

Initial cooldown time (LHe to 5 K)	~30 min	
Temperature range	3.5 K to 475 K	<6 K to 475 K
Typical temperature stability ¹	±50 mK	
Orientation ²	Any	
Cryogen consumption (LHe room to base temp)	~1 L	
Cryogen consumption (LHe at 5 K)	1.1 L/h	2.5 L/h (at 6 K)
Cryogen consumption (LHe at 10 K)	0.5 L/h	0.8 L/h
Cryogen consumption (LHe at 20 K)	0.2 L/h	0.4 L/h
Cryogen consumption (LN ₂ at 80 K)	0.1 L/h	0.1 L/h
Initial vacuum level requirement ³	~10 ⁻⁴ Torr	
Typical base pressure during operation	~10 ⁻⁵ Torr	
Nominal vibration amplitude	±10 nm	
Positional drift	±2 nm/min	

Size


Height	67 mm (2.62 in)	29.5 mm (1.16 in)
Inner diameter (at sample region)	73 mm (2.9 in)	59 mm (2.3 in)
Sample mount diameter	19.05 mm (0.75 in)	
Weight (excluding transfer line)	3.2 kg (7 lb)	2.3 kg (5 lb)
Shipping weight (cryostat only)	8.6 kg (19 lb)	
Shipping weight (transfer line)	9.1 kg (20 lb)	
Shipping dimensions (cryostat only)	762 × 508 × 508 mm (30 × 20 × 20 in)	
Shipping dimensions (transfer line)	2057.4 × 660.4 × 127 mm (81 × 26 × 5 in)	

¹ Measured with temperature controller

² Cryogen consumption may be higher during non-vertical operation

³ Pressure measured at room temperature, prior to adding cryogens

Typical vibration of an ST-500 sample mount at 4.2 K



Ordering information

Options

Windows

Custom window options are available, including IR-grade fused silica, diamond, polyethylene, beryllium (dome or disc), KBr, or KRS-5. Contact Lake Shore for more information.

WT-ST-500-062-FS	UV-grade fused silica, 10 mm clear view by 0.5 mm thick
WT-ST-500-062-ZNSE	ZnSe, 25 mm clear view by 1.6 mm thick
WT-ST-500-020-SAPH	Sapphire, 25 mm clear view by 0.5 mm thick
WT-ST-500-080-CAF2	CaF ₂ , 25 mm clear view by 2 mm thick

Snout extension

ST-500-EXT-PM	For permanent magnet
ST-500-EXT-SCON	For bore of superconducting magnet
CONSULT	For pole gap of electromagnet

Other options

The modular ST-500 cryostat can be customized with different vacuum shroud designs to suit your unique application. Options include adding a large vacuum shroud extension (ST-500-LGV) for added space inside the sample area, or the addition of nanopositioners (ST-500-NANO). Special sample holders are also available. Consult Lake Shore sales to discuss your specific requirement.

WT-ST-500-SHIELD	Cooled radiation shield window (ST-500 only)
-------------------------	--

Sample holders

CONSULT	DIP (with cooled radiation shield window)
CONSULT	Diamond anvil cell (DAC) or resistivity options

Electrical feedthroughs

EF-BNC-1-B-AL	(1) BNC grounded
EF-BNC-2-S-AL	(2) BNC grounded
EF-BNC-6-G	(6) BNC grounded
EF-BNC-1-B-NC	(1) BNC insulated
EF-BNC-2-S-NC	(2) BNC insulated
EF-BNC-6-I	(6) BNC insulated
EF-TRIAx-1-B-AL	(1) triaxial grounded
EF-TRIAx-6-G	(6) triaxial grounded
EF-TRIAx-1-B-NC	(1) triaxial insulated
EF-TRIAx-6-I	(6) triaxial insulated
EF-SMA-2-B-AL	(2) SMA grounded
EF-SMA-6-G	(6) SMA grounded
EF-SMA-2-B-NC	(2) SMA insulated
EF-SMA-6-I	(6) SMA insulated
10P-ASSEMBLY	10-pin
19P-ASSEMBLY	19-pin
26P-ASSEMBLY	26-pin
32P-ASSEMBLY	32-pin

Additional temperature sensors

DT-670-CU-HT-1.4L	Silicon diode, calibrated (one included with cryostat)
CX-1050-CU-HT-1.4M	Cernox® magnetic field independent, calibrated

Installed wiring

CABLEASSY-63340	(1), (2), or (6) coaxial cables, SMA
CABLEASSY-63342	(1), (2), or (6) coaxial cables, BNC
CABLEASSY-63341	(1) or (6) triaxial cables
WIRE-PHBR	(10), (19), (26), or (32) PhBr wires

Accessories

M81-SSM electronic synchronous source measure system

Contact us for standard/optical sample mounts or for interface cables/adapters for M81-SSM system/cryostat integration. Also available: specially priced preconfigured M81-SSM/cryostat packages for certain cryostat models—contact Sales for details.

M81-SSM-2	M81-SSM instrument with 1 source and 1 measure channel, including M81-SSM accessory kit (USB-A to USB-C adapter, USB-A male to USB-B male cable, terminal connectors for digital I/O, terminal connectors for chassis ground, quick-start guide) and a 2 m (6.6 ft) LEMO to BNC adapter cable
M81-SSM-4	M81-SSM instrument with 2 source and 2 measure channels, including M81-SSM accessory kit (USB-A to USB-C adapter, USB-A male to USB-B male cable, terminal connectors for digital I/O, terminal connectors for chassis ground, quick-start guide) and a 2 m (6.6 ft) LEMO to BNC adapter cable
M81-SSM-6	M81-SSM instrument with 3 source and 3 measure channels, including M81-SSM accessory kit (USB-A to USB-C adapter, USB-A male to USB-B male cable, terminal connectors for digital I/O, terminal connectors for chassis ground, quick-start guide) and a 2 m (6.6 ft) LEMO to BNC adapter cable
ML-MCS	MeasureLINK-MCS software with scripting development license. Includes complete MeasureLINK installation with Lake Shore instrument drivers, chart recorder functionality and drag-and-drop measurement sequences. Some application packs sold separately.

Other accessories

CF-100	100 L LHe storage Dewar
LN-50	50 L LN ₂ storage Dewar
10RVP	Vacuum pumping station
10DDP	Vacuum pumping station
TS-85-D	Turbomolecular pumping station
336	Model 336 temperature controller
335	Model 335 temperature controller
325	Model 325 temperature controller



Copyright © Lake Shore Cryotronics, Inc. All rights reserved. Specifications are subject to change.

011623 12:47

www.lakeshore.com



environment by  JANIS

Woburn location

225 Wildwood Avenue
Woburn, MA 01801-2025
Tel: +1 781 491 0888

Westerville headquarters

575 McCorkle Blvd
Westerville, OH 43082-8699
Tel: +1 781 491 0888

sales@lakeshore.com